

**BOSCH**

Invented for life

**SAFETY DATA SHEET****1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER****1.1 Product identifier**

**Product name** VALVE REGULATED, LEAD ACID – AGM  
**Synonyms** M6 MEGA POWER RIDE (MOTORCYCLE BATTERY)

**1.2 Uses and uses advised against**

**Uses** BATTERIES

**1.3 Details of the supplier of the product**

**Supplier name** ROBERT BOSCH AUSTRALIA PTY LTD  
**Address** 1555 Centre Rd, Clayton, VIC, 3168, AUSTRALIA  
**Telephone** (03) 9541 5555  
**Fax** (03) 9541 5595  
**Website** <http://www.bosch.com.au>

**1.4 Emergency telephone numbers**

**Emergency** 13 11 26 (24/7 Poisons Information Hotline)

**2. HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture**

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

**Physical Hazards**

Not classified as a Physical Hazard

**Health Hazards**

Skin Corrosion/Irritation: Category 1A  
Serious Eye Damage / Eye Irritation: Category 1  
Germ Cell Mutagenicity: Category 2  
Carcinogenicity: Category 2  
Toxic to Reproduction: Category 1A  
Specific Target Organ Toxicity (Repeated Exposure): Category 2

**Environmental Hazards**

Aquatic Toxicity (Chronic): Category 1

**2.2 GHS Label elements**

**Signal word** DANGER

**Pictograms****Hazard statements**

H314 Causes severe skin burns and eye damage.  
H318 Causes serious eye damage.  
H341 Suspected of causing genetic defects.  
H351 Suspected of causing cancer.  
H360Df May damage the unborn child. Suspected of damaging fertility.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H410 Very toxic to aquatic life with long lasting effects.

## PRODUCT NAME VALVE REGULATED, LEAD ACID – AGM

### Prevention statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

### Response statements

P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P310	Immediately call a POISON CENTRE or doctor/physician.
P321	Specific treatment is advised - see first aid instructions.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.

### Storage statements

P405	Store locked up.
------	------------------

### Disposal statements

P501	Dispose of contents/container in accordance with relevant regulations.
------	--

### 2.3 Other hazards

No hazards occur during the normal operation of a lead acid battery as it is described in the instructions for use that are provided with the battery. Lead-acid batteries have three significant characteristics:

- \* They contain an electrolyte which contains dilute sulphuric acid. Sulphuric acid may cause severe chemical burns.
- \* During the charging process or during operation they might develop hydrogen gas and oxygen, which under certain circumstances may result in an explosive mixture.
- \* They can contain a considerable amount of energy, which may be a source of high electrical current and a severe electrical shock in the event of a short circuit.

Used battery may also contain lead contaminated acid. Lead sulfate is often seen in the plates/electrodes of car batteries, as it is formed when the battery is discharged. When the battery is recharged, then the lead sulfate is transformed back to metallic lead and sulfuric acid on the negative terminal or lead dioxide and sulfuric acid on the positive terminal. Lead sulfate is toxic by inhalation, ingestion and skin contact. It is classified as a known or presumed human reproductive or developmental toxicant and causes damage to organs. Lead and lead sulphate is classified as very toxic to aquatic life with long lasting effects.

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS

### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
INORGANIC LEAD/ LEAD COMPOUNDS	7439-92-1	231-100-4	69.8%
DILUTE SULPHURIC ACID	7664-93-9	231-639-5	23.95%
GLASS, OXIDE	65997-17-3	266-046-0	1.1%
TIN	7440-31-5	231-141-8	0.45%
CALCIUM	7440-70-2	231-179-5	0.1%
2-PROPENENITRILE, POLYMER WITH 1,3-BUTADIENE AND ETHENYLBENZENE	9003-56-9	618-371-8	<4.6%
POLYPROPYLENE	9003-07-0	618-352-4	<4.6%

**Ingredient Notes** The materials contained in this product may only represent a hazard if the integrity of the cell or battery is compromised; physically or electrically abused.

## 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

<b>Eye</b>	Exposure to contents: If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
<b>Inhalation</b>	Exposure to contents: If inhaled, remove from contaminated area. To protect rescuer, use a Type B (Inorganic and acid gas) respirator where an inhalation risk exists. Apply artificial respiration if not breathing.
<b>Skin</b>	Exposure to contents: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair

## PRODUCT NAME VALVE REGULATED, LEAD ACID – AGM

with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

**Ingestion** For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.

**First aid facilities** Eye wash facilities and safety shower are recommended.

### **4.2 Most important symptoms and effects, both acute and delayed**

The electrolyte is corrosive and may cause irritation or severe chemical burns. Lead is a cumulative poison and has the potential to cause chronic health effects. Chronic exposure may result in blood, kidney and central nervous system/brain damage. Lead is classified as possibly carcinogenic to humans (IARC Group 2B). May cause harm to the unborn child. Possible risk of impaired fertility.

### **4.3 Immediate medical attention and special treatment needed**

Treat symptomatically.

---

## **5. FIRE FIGHTING MEASURES**

### **5.1 Extinguishing media**

Use an extinguishing agent suitable for the surrounding fire.

### **5.2 Special hazards arising from the substance or mixture**

Non flammable. Liquid component may evolve flammable hydrogen gas upon contact with metals. The potential for fire - explosion does exist through short circuit of terminals.

### **5.3 Advice for firefighters**

Treat as per requirements for surrounding fires. Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

### **5.4 Hazchem code**

2R  
2 Fine Water Spray.  
R Wear liquid-tight chemical protective clothing and breathing apparatus. Dilute spill and run-off.

---

## **6. ACCIDENTAL RELEASE MEASURES**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Contact emergency services where appropriate.

### **6.2 Environmental precautions**

Prevent product from entering drains and waterways.

### **6.3 Methods of cleaning up**

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

### **6.4 Reference to other sections**

See Sections 8 and 13 for exposure controls and disposal.

---

## **7. HANDLING AND STORAGE**

### **7.1 Precautions for safe handling**

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas. Keep from all metallic articles that could contact the negative and positive terminals on a battery and create a short circuit condition.

### **7.2 Conditions for safe storage, including any incompatibilities**

Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate ventilation systems. Due to the battery's low internal resistance and high power density, high levels of short circuit current can be developed across the battery terminals. Do not rest tools or cables on the battery. Use insulated tools only. Follow all installation instructions and diagrams when installing or maintaining battery systems.

### **7.3 Specific end uses**

No information provided.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

#### Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Acrylonitrile	SWA [AUS]	2	4.3	--	--
Lead, inorganic dusts & fumes (as Pb)	SWA [AUS]	--	0.05	--	--
Non-respirable fibres, inspirable dust	SWA [AUS]	--	2	--	--
Sulphuric acid	SWA [AUS]	--	1	--	3
Sulphuric acid	SWA [Proposed]	--	0.1	--	--
Synthetic mineral fibres, respirable fibres	SWA [AUS]	--	0.5 f/ml	--	--
Tin, metal	SWA [AUS]	--	2	--	--

#### Biological limits

Ingredient	Reference	Determinant	Sampling Time	BEI
LEAD	ACGIH BEI	Lead in blood	Not critical	200 µg/L
	ACGIH BEI	Lead in blood (women of child bearing potential)	Not critical	10 µg/100ml
	SWA [AUS]	Lead in blood	Not critical	30 µg/dL
	SWA [AUS]	Lead in blood (women of child bearing potential)	Not critical	10 µg/dL

### 8.2 Exposure controls

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.

#### PPE

- Eye / Face** Wear safety glasses.
- Hands** Wear PVC or rubber gloves.
- Body** Not required under normal conditions of use.
- Respiratory** Where an inhalation risk exists, wear a Type B (acid gas and vapours) respirator.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	SOLID (BATTERY)
Odour	ODOURLESS
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
pH	NOT AVAILABLE
Vapour density	NOT AVAILABLE
Relative density	NOT AVAILABLE
Solubility (water)	INSOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT AVAILABLE
Lower explosion limit	NOT AVAILABLE
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE

**9.1 Information on basic physical and chemical properties**

Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

**10. STABILITY AND REACTIVITY**

**10.1 Reactivity**

Carefully review all information provided in sections 10.2 to 10.6.

**10.2 Chemical stability**

Stable under recommended conditions of storage.

**10.3 Possibility of hazardous reactions**

Hazardous polymerisation is not expected to occur.

**10.4 Conditions to avoid**

Avoid heat, sparks, open flames and other ignition sources.

**10.5 Incompatible materials**

Incompatible with oxidising agents (e.g. hypochlorites), alkalis (e.g. sodium hydroxide), heat and ignition sources.

**10.6 Hazardous decomposition products**

May evolve toxic gases if heated to decomposition.

**11. TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects**

**Acute toxicity** Exposure to battery contents may result in severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach. Lead compounds are expected to be harmful if swallowed, in contact with skin, and/or if inhaled.

**Information available for the ingredients:**

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
INORGANIC LEAD/ LEAD COMPOUNDS	50 mg/kg to 600 mg/kg (calf)	--	--
DILUTE SULPHURIC ACID	2140 mg/kg (rat)	--	18 mg/m <sup>3</sup> (guinea pig); 510 mg/m <sup>3</sup> /2hrs (rat)

**Skin** Due to product encapsulation, the potential for skin contact with contents is reduced. If the container is damaged, contact may result in irritation, redness, pain, rash, dermatitis and possible burns. Effects may be delayed.

**Eye** Due to product encapsulation, the potential for eye contact with contents is reduced. If the container is damaged, direct contact may result in irritation, lacrimation and burns.

**Sensitisation** Not classified as causing skin or respiratory sensitisation.

**Mutagenicity** Due to product encapsulation, the potential for contact with contents is reduced. If the container is damaged, contact with contents is suspected of causing genetic defects.

**Carcinogenicity** Due to product encapsulation, the potential for exposure to the contents is reduced. Occupational exposure to strong inorganic acid mists containing sulphuric acid is classified as carcinogenic to humans (IARC Group 1). Lead compounds (inorganic) are classified as probably carcinogenic to humans (IARC Group 2A).

**Reproductive** Due to product encapsulation, the potential for exposure to the contents is reduced. Exposure to high levels of lead and its compounds may cause adverse effects on male and female fertility, including adverse effects on sperm quality. Prenatal exposure to lead and its compounds is also associated with adverse effects on neurobehavioral development in children.

**STOT - single exposure** Due to product encapsulation, the potential for exposure is unlikely. If the container is damaged, inhalation may result in mucous membrane irritation of the respiratory tract, coughing and inflammation. High level exposure may result in ulceration of the respiratory tract and lung tissue damage.

**STOT - repeated exposure** Due to product encapsulation, the potential for exposure to the contents is reduced. Lead is a cumulative poison and may be absorbed into the body through ingestion or inhalation. Lead has been documented in observational human studies to produce toxicity in multiple organ systems and body function including the haematopoietic (blood) system, kidney function, reproductive function and the central nervous system.

**Aspiration** Not classified as causing aspiration.

## 12. ECOLOGICAL INFORMATION

### 12.1 Toxicity

Lead is potentially toxic to all aquatic organisms, with organic lead compounds tending to be more toxic than inorganic lead compounds. Lead becomes more toxic to fish as dissolved oxygen levels decrease. Toxicity to aquatic organisms increases in acidic or soft water.

### 12.2 Persistence and degradability

Inorganic lead does not degrade.

### 12.3 Bioaccumulative potential

Lead bioconcentrates and bioaccumulates in both aquatic and terrestrial organisms.

### 12.4 Mobility in soil

Lead is sparingly soluble and is expected to be adsorbed onto soils and sediments. Mobility is expected to be low.

### 12.5 Other adverse effects

No information provided.

## 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

**Waste disposal** This product is recyclable. Please return to manufacturer. Contact the manufacturer/supplier for additional information (if required).

**Legislation** Dispose of in accordance with relevant local legislation.

## 14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	2800	2800	2800
14.2 Proper Shipping Name	BATTERIES, WET, NON-SPILLABLE, electric storage	BATTERIES, WET, NON-SPILLABLE, electric storage	BATTERIES, WET, NON-SPILLABLE, electric storage
14.3 Transport hazard class	8	8	8
14.4 Packing Group	None allocated.	None allocated.	None allocated.

### 14.5 Environmental hazards

Not a Marine Pollutant.

### 14.6 Special precautions for user

Hazchem code	2R
GTEPG	8A1
EmS	F-A, S-B

**Other information** These batteries are non-spillable and meet the requirements of IATA Special Provision A67, IMDG 238.1 and 238.2, ADG 238 and NZS 5433 DG Special Provision 238 provided, when packaged for transport, the terminals are protected from short circuit. This means, for example, exemption from road transport placarding requirements.

## 15. REGULATORY INFORMATION

## PRODUCT NAME VALVE REGULATED, LEAD ACID – AGM

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>Poison schedule</b>	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
<b>Classifications</b>	Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).
<b>Inventory listings</b>	<b>AUSTRALIA: AIC (Australian Inventory of Industrial Chemicals)</b> All components are listed on AIC, or are exempt.

---

## 16. OTHER INFORMATION

---

**Additional information**      RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

ACIDS: When mixing acids with water (diluting), caution must be taken as heat will be generated which causes violent spattering. Always add a small volume of acid to a large volume of water, NEVER the reverse.

#### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

#### HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

<b>Abbreviations</b>	ACGIH	American Conference of Governmental Industrial Hygienists
	CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
	CNS	Central Nervous System
	EC No.	EC No - European Community Number
	EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
	GHS	Globally Harmonized System
	GTEPG	Group Text Emergency Procedure Guide
	IARC	International Agency for Research on Cancer
	LC50	Lethal Concentration, 50% / Median Lethal Concentration
	LD50	Lethal Dose, 50% / Median Lethal Dose
	mg/m <sup>3</sup>	Milligrams per Cubic Metre
	OEL	Occupational Exposure Limit
	pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
	ppm	Parts Per Million
	STEL	Short-Term Exposure Limit
	STOT-RE	Specific target organ toxicity (repeated exposure)
	STOT-SE	Specific target organ toxicity (single exposure)
	SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
	SWA	Safe Work Australia
	TLV	Threshold Limit Value
	TWA	Time Weighted Average

**PRODUCT NAME VALVE REGULATED, LEAD ACID – AGM**

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmt.com.au](mailto:info@rmt.com.au)  
Web: [www.rmtglobal.com](http://www.rmtglobal.com)

**[ End of SDS ]**