

We know what is the **best** for your engine

As a global automotive technology supplier with more than a hundred year history, we strive to provide you with exceptional protection for vehicle of all ages against engine wear, sludge and harmful deposits, even under some of the most extreme temperature and driving conditions, especially at higher temperature in tropical region.

Boosting the latest and premium base oil technology and fulfilled API standards, the Bosch new lubricant line ensures that your engine stays in optimum condition over a much longer period and has the strength to push the boundaries of performance.





The Bosch **Advantages**

- ▶ Core differentiator: Superior base oils used in mineral (Group II), semi-synthetic (Group II + Group III) and fully synthetic lines (Group III + PAO) for dominant benefits in oxidation stability and Viscosity Index.
- ▶ Designed to optimize engine protection over a much wider temperature range especially at higher temperature in the tropical region.
- ▶ Extending service life of your car engine with higher oxidation stability.
- ▶ Certified to the governing automotive industry standards: A tradition of trust for more than 125 years.
- ▶ The Bosch distribution network provides a one-stop-shop automotive solution at every sales point.



SN 0W30 Ultra X8

Fully Synthetic Engine Oil



Bosch Part Number:
1987L24080

Capacity: 4L

Product Features

- ▶ Premium base oil used - PAO
- ▶ Excellent dynamic lubrication with advanced technology for real time protection
- ▶ Enhanced lubrication effectiveness across various driving conditions and temperatures
- ▶ Exceptional viscosity stability over varying temperatures for high performance consistency
- ▶ Prolongs service life due to superior oxidation stability
- ▶ Reduces engine deposits with outstanding cleaning performance
- ▶ Fulfills the stringent GF-5 requirements for excellent fuel efficiency

Application

Recommended for premium sedans, sports and racing cars especially those with turbocharged engines.

Specification

API SN certified, ILSAC GF-5 fulfilled

Test Description	Method	Unit	Typical Results
SAE Viscosity Grade	SAE J 300	-	0W30
Specific Gravity @ 15°C	ASTM D 4052	kg/l	0.872
Flash Point	ASTM D 92	°C	214
Pour Point	ASTM D 97	°C	-42
Kinematic Viscosity @ 40°C @ 100°C	ASTM D 445	cSt	55.3
	ASTM D 445	cSt	10.2
Viscosity Index	ASTM D 2270	-	175
TBN, (mgKOH/g)	ASTM D 2896	mgKOH/g	7.8
Color	ASTM D 1500	-	<3.0



SN 0W40 Ultra X8

Fully Synthetic Engine Oil



Bosch Part Number:
1987L24083

Capacity: 4L

Product Features

- ▶ Premium base oil used - PAO
- ▶ Excellent dynamic lubrication with advanced technology for real time protection
- ▶ Enhanced lubrication effectiveness across various driving conditions and temperatures
- ▶ Exceptional viscosity stability over varying temperatures for high performance consistency
- ▶ Prolongs service life due to superior oxidation stability
- ▶ Reduces engine deposits with outstanding cleaning performance

Application

Recommended for premium sedans, sports and racing cars especially those with turbocharged engines.

Specification

API-SN certified

Test Description	Method	Unit	Typical Results
SAE Viscosity Grade	SAE J 300	-	0W40
Specific Gravity @ 15°C	ASTM D 4052	kg/l	0.8508
Flash Point	ASTM D 92	°C	218
Pour Point	ASTM D 97	°C	-42
Kinematic Viscosity @ 40°C @ 100°C	ASTM D 445	cSt	77.36
	ASTM D 445	cSt	13.66
Viscosity Index	ASTM D 2270	-	182
TBN, (mgKOH/g)	ASTM D 2896	mgKOH/g	10
Color	ASTM D 1500	-	<3.0



SN 5W30 Premium X7

Fully Synthetic Engine Oil

Product Features

- ▶ Excellent dynamic lubrication with advanced technology for real time protection
- ▶ Enhanced lubrication effectiveness across various driving conditions and temperatures
- ▶ Exceptional viscosity stability across varying temperatures for high performance consistency
- ▶ Prolongs service life due to superior oxidation stability
- ▶ Unique formula to protect exhaust system and to meet stringent emission requirements
- ▶ Fulfills the stringent GF-5 requirements for excellent fuel efficiency

Application

Recommended for vehicles with turbocharger, compressed natural gas and gasoline engines for premium sedan and light truck.

Specification

API SN certified, ILSAC GF-5 fulfilled



Bosch Part Number:
1987L24070

Capacity: 4L

Test Description	Method	Unit	Typical Results
SAE Viscosity Grade	SAE J 300	-	5W30
Specific Gravity @ 15°C	ASTM D 4052	kg/l	0.874
Flash Point	ASTM D 92	°C	216
Pour Point	ASTM D 97	°C	-39
Kinematic Viscosity @ 40°C @ 100°C	ASTM D 445	cSt	54.9
	ASTM D 445	cSt	9.66
Viscosity Index	ASTM D 2270	-	162
TBN, (mgKOH/g)	ASTM D 2896	mgKOH/g	7.8
Color	ASTM D 1500	-	<3.0



SN 5W40 Premium X7

Fully Synthetic Engine Oil

Product Features

- ▶ Excellent dynamic lubrication with advanced technology for real time protection
- ▶ Enhanced lubrication effectiveness across various driving conditions and temperatures
- ▶ Exceptional viscosity stability across varying temperatures for high performance consistency
- ▶ Prolongs service life due to superior oxidation stability
- ▶ Unique formula to protect exhaust system and to meet strict emission requirements

Application

Recommended for vehicles with turbocharger, compressed natural gas and gasoline engines for premium sedan and light truck.

Specification

API-SN certified



Bosch Part Number:
1987L24073

Capacity: 4L

Test Description	Method	Unit	Typical Results
SAE Viscosity Grade	SAE J 300	-	5W40
Specific Gravity @ 15°C	ASTM D 4052	kg/l	0.856
Flash Point	ASTM D 92	°C	216
Pour Point	ASTM D 97	°C	-39
Kinematic Viscosity @ 40°C @ 100°C	ASTM D 445	cSt	89.9
	ASTM D 445	cSt	14.5
Viscosity Index	ASTM D 2270	-	168
TBN, (mgKOH/g)	ASTM D 2896	mgKOH/g	7.8
Color	ASTM D 1500	-	<3.0



SN 10W30 Mega X6

Semi Synthetic Engine Oil

Product Features

- ▶ Superior detergency and dispersion properties that reduces the generation of engine deposits
- ▶ Superior viscosity stability for consistently high performance across all seasons
- ▶ Reduction of early stage engine wear with good cold-start performance
- ▶ Fuel saving properties engineered through unique formula
- ▶ Excellent oxidation resistance against sludge formation
- ▶ Good compatibility with all gaskets and sealing materials to prevent oil leaks

Application

Recommended for medium to high end vehicle range.

Specification

API SN certified, ILSAC GF-5 fulfilled



Bosch Part Number:
1987L24060

Capacity: 4L

Test Description	Method	Unit	Typical Results
SAE Viscosity Grade	SAE J 300	-	10W30
Specific Gravity @ 15°C	ASTM D 4052	kg/l	0.8502
Flash Point	ASTM D 92	°C	214
Pour Point	ASTM D 97	°C	-36
Kinematic Viscosity @ 40°C @ 100°C	ASTM D 445	cSt	67.91
	ASTM D 445	cSt	11.11
Viscosity Index	ASTM D 2270	-	156
TBN, (mgKOH/g)	ASTM D 2896	mgKOH/g	6.8
Color	ASTM D 1500	-	<3.0



SN 10W40 Mega X6

Semi Synthetic Engine Oil

Product Features

- ▶ Superior detergency and dispersion properties that reduces the generation of engine deposits
- ▶ Superior viscosity stability for consistently high performance across all seasons
- ▶ Reduction of early stage engine wear with good cold-start performance
- ▶ Fuel saving properties engineered through unique formula
- ▶ Excellent oxidation resistance against sludge formation
- ▶ Good compatibility with all gaskets and sealing materials to prevent oil leaks

Application

Recommended for medium to high end vehicle range

Specification

API-SN certified



Bosch Part Number:
1987L24063

Capacity: 4L

Test Description	Method	Unit	Typical Results
SAE Viscosity Grade	SAE J 300	-	10W40
Specific Gravity @ 15°C	ASTM D 4052	kg/l	0.8597
Flash Point	ASTM D 92	°C	214
Pour Point	ASTM D 97	°C	-36
Kinematic Viscosity @ 40°C @ 100°C	ASTM D 445	cSt	88.6
	ASTM D 445	cSt	13.85
Viscosity Index	ASTM D 2270	-	160
TBN, (mgKOH/g)	ASTM D 2896	mgKOH/g	6.8
Color	ASTM D 1500	-	<3.0

